



PRODUCT FEATURES

MARIN-T MARINE OILS

MARIN-T paraffinic based mineral base oils produced sulfur content of 1% of the fuel is used up recommended for medium and high speed diesel engines, high-performance marine diesel engine oil.

APPLICATIONS

Vessels are the most important places auxiliary diesel machines. In addition, working in extreme conditions on board fishing vessels, especially low-fat high-volume and high-speed diesel engines performance.

TECHNICAL SPECIFICATIONS

- High and medium speed diesel engines, main and auxiliary machinery
- Stern tube and gear boxes, lubrication of turbocharger
- SAE 30 or SAE 40 ships deck or other lubrication points, recommended

PERFORMANCE

API: CF

| SAE | 40 | 30 |
|-------------------------------------|-------|-------|
| Density 15 °C g/mL | 0,897 | 0,900 |
| Viscosity 40 °C, mm ² /s | 104 | 139 |
| Viscosity 100 °C mm ² /s | 11,8 | 14,4 |
| TBN mg KOH/g | 12 | 12 |
| Pour Point °C | -18 | -18 |

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments