

PRODUCT FEATURES

ULTRAGEAR EP 75W-90

ULTRAGEAR EP 75W-90 paraffinic base oils, produced by the addition of a special multi-grade gear oil additive package. Especially developed for hypoid type gear boxes, multigrade gear oil suitable for use in all four seasons.

Applications

Exposed to extreme pressure, high speed and cars, heavy duty trucks and construction machinery gearboxes and differentials with hypoid, bevel and helical gear systems. High-performance heavy-duty automotive gear oil.

performance

API: GL-4

application

- Heavy and impact loads, vibration shows the high performance working conditions,
- High operating temperatures provides superior protection against wear and tear,
- Multigrade properties and can be used safely in all four seasons,
- fluidity at low temperatures, preserving the life of the equipment, especially the first studies extend,
- Corrosion and rust preventive additives protects the surface of the gear,
- extending oil change periods, reduces maintenance costs

Typical Properties

Density 15 °C g/mL	0.874
Viscosity 40 °C, mm ² /s	72
Viscosity 100 °C mm ² /s	14.1
Viscosity Index	96
Flash Point° C	210

PACKAGING

20 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.