



## PRODUCT FEATURES

### ULTRAGEAR 90 GL-1

ULTRAGEAR paraffinic base oils produced in 90 low ash-free mineral gear oil.

#### Applications

Working under normal conditions does not require overload and pressure characteristics of automotive and industrial equipment, mineral oils used in gearboxes and differentials. Gear units working under very heavy loads, manual synchromesh gearboxes and differentials are used.

#### Technical Specifications

- Compatible with all types of metal and seal work,
- Due to the high viscosity index, viscosity at operating temperatures, protects minimal amounts of wear and tear during the first study,
- wear, rust and anti-corrosion properties provides effective protection thanks to the metal loss Does not.
- Long service life.

#### performance

API GL-1

#### Typical Properties

Density 15 °C g/mL	0.896
Viscosity 40 °C, mm <sup>2</sup> /s	180
Viscosity 100 °C mm <sup>2</sup> /s	14
Viscosity Index	92
Flash Point° C	190

#### PACKAGING PACKAGING

3L	Plastic
4 L	Plastic
15 kg	TIN
180 kg	DRUM

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



## PRODUCT FEATURES

---

