



PRODUCT FEATURES

SUPER ATF DEXRON II

SUPER ATF DEXRON II high viscosity index paraffinic mineral base oils, automatic transmission fluid is produced.

Applications

Passenger cars and commercial vehicles, heavy vehicles, such as buses and trucks used in transmissions, power steering systems and other hydraulic applications.

Technical Specifications

- With friction modifier feature allows smooth and easy power transmission,
- compatible with all sealing elements,
- facilitate follow-up and release the clutch increases the efficiency of transmission,
- Low temperatures kalınlaşmaz provides convenience and power transmission
- rust, corrosion, shows superior protection against wear and tear,
- Foam create a
- Long service life.

performance

Dextron IID

Ford mecro

Allison C-4,

Caterpillar TQ2

Denison HF-0

Typical Properties

| | |
|-------------------------------------|-------|
| Density 15 °C g/mL | 0.867 |
| Viscosity 40 °C, mm ² /s | 43 |
| Viscosity 100 °C mm ² /s | 7,2 |
| Viscosity Index | 150 |
| Flash Point° C | 180 |
| Pour Point, ° C | -40 |

PACKAGING

| | |
|--------|---------|
| 1L | Plastic |
| 3L | Plastic |
| 4 L | Plastic |
| 16 kg | TIN |
| 180 kg | DRUM |

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



PRODUCT FEATURES

