



PRODUCT FEATURES

ULTRAGEAR EP 85W/140 GL-5

ULTRAGEAR EP 85W/140 paraffinic base oils, produced by the addition of a special multi-grade gear oil additive package. Especially developed for hypoid type gear boxes, multigrade gear oil suitable for use in all four seasons

Applications

Exposed to extreme pressure, high speed and cars, heavy duty trucks and construction machinery gearboxes and differentials with hypoid, bevel and helical gear systems. High-performance heavy-duty automotive gear oil.

Technical Specifications

- Heavy and impact loads, vibration shows the high performance working conditions,
- High operating temperatures provides superior protection against wear and tear,
- Multigrade properties and can be used safely in all four seasons,
- fluidity at low temperatures, preserving the life of the equipment, especially the first studies extend,
- Corrosion and rust preventive additives protects the surface of the gear,
- extending oil change periods, reduces maintenance costs.

performance

API GL-5

Typical Properties

Density 15 °C g/mL	0.910
Viscosity 40 °C, mm ² /s	428
Viscosity 100 °C mm ² /s	29
Viscosity Index	95
Flash Point° C	222
Pour Point, ° C	-18

PACKAGING

4L	PLASTIC
15kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.