



PRODUCT FEATURES

ULTRAGEAR EP 90 GL-4

ULTRAGEAR paraffinic mineral base oils and EP 90 with knife-functional additive package formulated EP gear oil that feature car.

Applications

Passenger cars and commercial vehicles, gear boxes, high speed, low torque and high speed, high torque, high performance in operating conditions. Sekromeçli gear boxes, proper pressure differentials kullanılması against the strong, overshooting and high resistance to corrosion, oxidation blocking feature.

performance

API: GL4

application

- Heavy and impact loads, vibration shows the high performance working conditions,
- High operating temperatures provides superior protection against wear and tear,
- Multigrade properties and can be used safely in all four seasons,
- fluidity at low temperatures, preserving the life of the equipment, especially the first studies extend,
- Corrosion and rust preventive additives protects the surface of the gear,
- extending oil change periods, reduces maintenance costs.

Typical Properties

Density 15 °C g/mL	0.904
Viscosity 40 °C, mm ² /s	145
Viscosity 100 °C mm ² /s	14,7
Viscosity Index	95
Flash Point° C	191
Pour Point, ° C	-18

PACKAGING

15kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.