



## PRODUCT FEATURES

### **BFLEX (LITHIUM COMPLEX GREASE BLUE)**

BFLEX paraffinic mineral base oil and lithium complex soap, reinforced polymers and EP characteristics as general purpose grease. Thanks to the increased viscosity of the grease to the surface of fiber.

#### **Applications**

Working in the field and in the business of dealing with a very difficult working conditions and agricultural machines, speed and high load bearings and sliding bearings operating under severe conditions, such as that developed for use in industrial applications. In addition, pressure, temperature, and high resistance against water suitable for use in all the required lubrication points.

#### **Technical Specifications**

- Centralized systems are easily pumped cold.
- wear, rust and provides superior protection against corrosion,
- Operating range temperature does not exceed 175 ° C gives good results in applications,
- High pressure and temperature resistance for long equipment life, extended grease life and has greasing intervals
- High bond strength provides a low-grease consumption.

#### **Typical Properties**

NLGI Numarası		2	3
Color		Blue	Blue
Soap Type		Lithium Complex	Lithium Complex
Penetration	25 °C/60 Stroke	265/295	220/250
Dropping Point ° C	°C	240	240
Base Oil		Mineral	Mineral
Base Oil Viscosity	40 °Cst	100	130
Base Oil Viscosity	100 °Cst	11	13
Operating Temperature	Max°C	-30 /150	-30 /150

#### **PACKAGING**

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

#### **Warnings and Suggestions**

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



**SAMPİYON**

## PRODUCT FEATURES

---

