



PRODUCT FEATURES

CAPENOL CL 3 (Complex Grease)

CL 3 lithium-calcium complex soap CAPENOL powered general purpose grease manufactured and special additives.

Applications

Sought out the yardstick for heavy duty and high temperature conditions required for systems. Different areas of the industry, especially in low and medium speed bearings and bearings. In addition, general lubrication applications, the automotive industry is also recommended.

Technical Specifications

- working conditions and high temperature properties of heavy applications is sought is preferred because of economical,
- Wear, providing superior protection against rust and corrosion, extending the life of the system used,
- Easy to pump,
- resistance against water,
- Long service life.

Typical Properties

NLGI Numarası		1	2	3
Color		White	White	White
Soap Type		Lithium-Calcium	Lithium-Calcium	Lithium-Calcium
Penetration	25 °C/60 Stroke	310/340	265/295	220/250
Dropping Point ° C	°C	140	145	150
Base Oil		Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	130	130	130
Base Oil Viscosity	100 °Cst	13	13	13
Operating Temperature	Max°C	-20 / +100	- 20/105	- 20/105

PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



PRODUCT FEATURES
