



PRODUCT FEATURES

GRENOL C (RUBBER GREASE)

GRENOL C 3 consisting of paraffinic mineral base oils and calcium soap grease with general purpose adhesive suitable for use.

Applications

Operating temperatures do not exceed 80 oC applied heavy loads at low speed rotating lubrication of bearings, chassis and other miscellaneous components used in greases general It is recommended for industrial use.

Technical Specifications

- With Korezyon chemicals used to increase the strength of the system does not flow adhered to,
- Provides superior protection,
- ease of use in different ranges of penetration,
- Easy to pump,
- resistance to water washout,
- Heavy work is sought out criteria for the systems are preferred due to economical,
- Other greases are painted green to decouple special.

Typical Properties

NLGI Numarası		1	2	3
Color		Green	Green	Green
Soap Type		Calcium	Calcium	Calcium
Penetration	25 °C/60 Stroke	310/340	265/295	220/250
Dropping Point ° C	°C	100	100	100
Base Oil		Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	220	220	220
Base Oil Viscosity	100 °Cst	19,4	19,4	19,4
Operating Temperature	Max°C	-10/80	-10/80	-10/80

PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



SAMPIYON

PRODUCT FEATURES

