



PRODUCT FEATURES

HIGH TEMP (LITHIUM COMPLEX)

HIGH TEMP lithium complex soap thickener and special additives enhanced by the addition of water to wash and heat resistance, improved resistance to impact loads grease containing EP additives.

Applications

Working in the field and in the business of dealing with a very difficult working conditions and agricultural machines, speed and high load bearings and sliding bearings operating under severe conditions, such as that developed for use in industrial applications. In addition, pressure, temperature, and high resistance against water suitable for use in all the required lubrication points.

Technical Specifications

- Centralized systems are easily pumped cold.
- wear, rust and provides superior protection against corrosion,
- Operating range temperature does not exceed 175 ° C gives good results in applications,
- High pressure and temperature resistance for long equipment life, extended grease life and has greasing intervals
- High bond strength provides a low-grease consumption.

Typical Properties

| NLGI Numarası | | 2 | 3 |
|-----------------------|-----------------|-----------------|-----------------|
| Color | | Brown | Brown |
| Soap Type | | Lithium Complex | Lithium Complex |
| Penetration | 25 °C/60 Stroke | 265/295 | 220/250 |
| Dropping Point ° C | °C | 260 | 260 |
| Base Oil | | Mineral | Mineral |
| Base Oil Viscosity | 40 °Cst | 160 | 160 |
| Base Oil Viscosity | 100 °Cst | 15,5 | 15,5 |
| Operating Temperature | Max°C | -30/130 | -30/130 |

PACKAGING

| | |
|--------|-------------|
| 1 kg | TIN BOX |
| 4 kg | TIN BOX |
| 16 kg | PAIL |
| 50 kg | MINI BARREL |
| 180 kg | DRUMS |

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.