



PRODUCT FEATURES

MOLYLUB EP (Molybdenum GREASE)

Consisting of high-quality base oil and lithium soap MOLYLUB EP also contains molybdenum disulfide (MoS₂) and EP under load due to vibration and provides superior protection by reducing friction and wear. Contains additives to prevent corrosion and oxidation.

Applications

Cars and commercial vehicles, off-road vehicles, construction machines can be used for general lubrication. 150 ° C operating temperature range of up to run smoothly. Also suitable for many industrial applications requiring molybdenum grease.

Technical Specifications

- in its structure Molybdenum disulfide (MoS₂), thanks to the heavy and providing additional protection against impact loads, vibration, immediately prevents metal to metal contact with,
- Excellent resistance to high temperatures and water,
- Wear, shows high resistance against rust and corrosion,
- Easy capable of pumping, the first easy lubrication during operation allows you to get points.
- providing effective protection, extends equipment life.

Typical Properties

NLGI Numarası		1	2	3
Color		Black	Black	Black
Soap Type		Lithium	Lithium	Lithium
Penetration	25 °C/60 Stroke	310/340	265/295	220/250
Dropping Point ° C	°C	190	200	200
Base Oil		Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	140	140	140
Base Oil Viscosity	100 °Cst	14,5	14,5	14,5
Operating Temperature	Max°C	-30 / 120	-30 /130	-30 /130
Four Ball Test		260	260	260

PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.