



PRODUCT FEATURES

PULSER C 3 (GRAPHITE GREASE)

PULSER C 3 calcium soap and gray. Thanks also contained graphite, especially high-vibration, heavy loads applied to rail vehicles and rail systems have been developed.

Applications

Used at operating temperatures do not exceed 80 oC. Automotive, construction machinery, iron and steel and mining industries, such as machinery wire rope, was developed for the lubrication of moving components, such as tapes and general purpose bearing grease.

Technical Specifications

- For systems without heavy working conditions and high temperature properties economical,
- Easy to pump,
- excellent resistance to water,
- It contains active components are high-vibration runs smoothly thanks to graphite,
- providing effective lubrication, extends the life of the equipment used.

Typical Properties

NLGI Numarası		1	2	3
Color		Gry	Gry	Gry
Soap Type		Calcium	Calcium	Calcium
Penetration	25 °C/60 Stroke	310/340	265/295	220/250
Dropping Point ° C	°C	105	105	105
Base Oil		Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	100	100	100
Base Oil Viscosity	100 °Cst	11	11	11
Operating Temperature	Max°C	-10/80	-10/80	-10/80

PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.