



## PRODUCT FEATURES

### ROLLER LT (BEARING GREASE)

ROLLER LT 3 quality mineral base oils and carefully selected additives, comprising suitable for use in multi-purpose, high-performance lithium greases.

#### Applications

Severe shock and the load does not require the use of a variety of industries are common. Applications operating temperatures do not exceed 150 ° C is recommended as soon as possible. Provides effective lubrication sliding surfaces, especially flat and rolling element bearings. Gresajında automotive-type equipment is available when needed.

#### Technical Specifications

- Very severe operating conditions, unwanted applications, gives better results,
- Oxidation, rust and anti-corrosion properties and protects metal surfaces,
- Excellent resistance to high temperatures and water,
- Easy to pump the trouble-free working environment, prevents corrosion,
- Thanks to the different ranges of penetration, the industry's ease of use in different areas of provides.
- Superior lubricity properties extends the life of the system.

#### Typical Properties

NLGI Numarası		000	00	0	1	2	3
Color		Light brown	Light brown	Light brown	Light brown	Light brown	Light brown
Soap Type		Lithium	Lithium	Lithium	Lithium	Lithium	Lithium
Penetration	25 °C/60 Stroke	400/430	400/430	385/355	310/340	265/295	220/250
Dropping Point ° C	°C	160	165	175	185	202	202
Base Oil		Mineral	Mineral	Mineral	Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	100	100	100	100	100	100
Base Oil Viscosity	100 °Cst	10	10	10	10	10	10
Operating Temperature	Max°C	-20 /+ 120	-20 /+ 120	-20 /+ 120	-20 /+ 130	-20 /+ 130	-20 /+ 130

#### PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.