



## PRODUCT FEATURES

### RUBYNOL C 3 (RED GREASE)

RUBYNOL C of paraffinic mineral base oils and calcium soap grease suitable for use in general purpose.

#### Applications

Severe operating conditions is not necessary and does not exceed the operating temperature of 80 ° C under normal load low speed plain bearings, agricultural and road machines. It is recommended for general industrial use.

#### Technical Specifications

- resistance to water washout,
- impermissibly high degree of stability in the Middle shows
- more economical for systems that are not severe working conditions,
- Easy to pump,
- having a different penetrasyonlara, ease of use in several areas,
- Other greases to decouple a special red color painted.

#### Typical Properties

NLGI Numarası		1	2	3
Color		Red	Red	Red
Soap Type		Calcium	Calcium	Calcium
Penetration	25 °C/60 Stroke	310/340	265/295	220/250
Dropping Point ° C	°C	100	100	100
Base Oil		Mineral	Mineral	Mineral
Base Oil Viscosity	40 °Cst	220	220	220
Base Oil Viscosity	100 °Cst	19,4	19,4	19,4
Operating Temperature	Max°C	-10/80	-10/80	-10/80

#### PACKAGING

1 kg	TIN BOX
4 kg	TIN BOX
16 kg	PAIL
50 kg	MINI BARREL
180 kg	DRUMS

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



SAMPİYON

## PRODUCT FEATURES

---

