



## PRODUCT FEATURES

### PRO-TORQUE 10W40 EXCEL

EXCEL PRO-TORQUE 10W40 mineral base oils and synthetic oils formulated with essential parafanik be blended with premium semi-synthetic diesel engine oil additive package.

#### Applications

All turbo-charged, high-powered, four-stroke engines and heavy-duty construction vehicles and severe operating conditions used in long-haul fleet.

#### Technical Specifications

- Thanks to the semi-synthetic oxidation resistance.
- Cylinder and piston ensures a clean,
- In cold conditions, minimizes wear study,
- High TBN values prevents the negative effects of burning fuel to protect the engine,
- Heavy road and climatic conditions provides the advantage of even longer oil change.

#### performance

API: SL / CI4    M. B. 223    MACK EO M PLUS  
ACEA-E7-04    MAN M 3275  
ACEA.B404    VOLVO VDS.3

#### Typical Properties

SAE	10W40
Viscosity 100 °C mm <sup>2</sup> /s	13,50
Viscosity 40 °C mm <sup>2</sup> /s	89,00
TBN mgKOH/g	14,20
Viscosity Index	155
Flash Point °C	225
Pour Point °C	-32

#### PACKAGING

20 L	TIN
180 kg	DRUM

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments