



PRODUCT FEATURES

PRO-TECH 10W/40

PRO-TECH 10W/40, be formulated with paraffinic base oils and high performance additives polialfaolin produced by the addition of a semi-synthetic motor oil.

Applications

All gasoline and diesel engines of passenger cars can be used safely in all four seasons. Dispersant, dioperansson, high-performance oil fortified with detergent additives.

Technical Specifications

- rust, corrosion and high protection against wear,
- Prevents oxidation,

performance

API: SL / CI4 M. B. 223 MACK EO M PLUS
ACEA-E7-04 MAN M 3275
ACEA.B404 VOLVO VDS.3

Typical Properties

SAE	10W/40
Density 15 °C g/mL	0.873
Viscosity 40 °C, mm ² /s	103
Viscosity 100 °C mm ² /s	14
Viscosity Index	156
Flash Point °C	224
Pour Point °C	-38

PACKAGING

1L	PLASTIC
4L	PLASTIC
5L	PLASTIC
180 kg	DRUM



PRODUCT FEATURES



Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments