



PRODUCT FEATURES

PRO-MAX 15W40

PRO-MAX 15W40 paraffinic based mineral base oils and performance additives produced with a superior feature a very high-tech diesel engine oil.

Applications

Working under very difficult conditions and all types of heavy vehicles turbo-charged and turbo discharged powerful four-stroke diesel engines used in construction and agricultural machines.

Technical Specifications

- Thermal stability and oxidation resistance is very high,
- prevents the formation of sludge, keeping the engine clean,
- Heavy climate and road conditions, pressure drop and protects the engine,
- Extends oil change time
- High detergent and dispersant prevents debris through the engine,

performance

API CI-4 / SL

ACEA E7-04 ACEA B4-04

228.3 MB

MAN M 3275

VOLVO VDS-3

CATERPILLAR ECF-1a

Typical Properties

SAE	15W40
Viscosity 100 °C mm ² /s	15,13
TBN mgKOH/g	11,50
Viscosity Index	131
Flash Point °C	224
Pour Point °C	-30

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments



PRODUCT FEATURES

