



PRODUCT FEATURES

SUPER ACTIVE 20W/50

SUPER ACTIVE 20W/50 diesel engines produced for all kinds of high-quality base oils and additives of superior qualities of engine oil.

Applications

Cars, trucks, buses and other vehicles as well as gasoline or diesel engines, construction machinery and agricultural machinery shows superior performance in all four seasons.

Technical Specifications

- providing effective lubrication, protects the motor, increasing performance,
- The first work in the cold makes it easier to provide adequate lubrication in hot weather thinning,
- With the help of high quality detergent-dispersant type additives to prevent sludge and deposits, the engine
Keeps a clean,
- wear, rust and oxidation inhibitors provide superior protection thanks to the engine,
- Prevents corrosion by neutralizing acids in the engine combustion residue,
- Pressure falls, foam, diminishes.

performance

API CF-4

Typical Properties

SAE	20W/50
Density 15 °C g/mL	0.897
Viscosity 40 °C, mm ² /s	201
Viscosity 100 °C mm ² /s	20
Viscosity Index	121
Flash Point °C	222
Pour Point °C	-15

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments



SAMPIYON

PRODUCT FEATURES

