



PRODUCT FEATURES

VENUS SERIES

VENUS SERIES formulated with mineral base oil and superior additive package used single-grade engine oil is normal and turbo-charged engines.

Applications

Construction machinery, diesel engines operating under severe conditions, driven industrial equipment, mining and construction equipment and in serving the construction industry in many diesel engines used in trucks. VENUS 10W oil in the hydraulic system oil business machines, VENUS 30 Tark convector oil, the oils VENUS 50 gear oil in the compartments as traction machines use some work area.

Technical Specifications

- High-dispersive feature of the system ensures a clean,
- Different viscosity grades are produced each season using the appropriate viscosity oil provides the opportunity,
- Provides long service life due to water separation characteristics
- additives contained the oxidation, rust and show high resistance to abrasion, extend the life of machinery and equipment,

performance

API CF	MAN 270
ALLISON C4	CAT TO-2
ACEA E2	MIL-L 2104 F

Typical Properties

SAE	10W	20W/20	30	40	50
Density 15 °C g/mL	0,885	0,890	0,890	0,895	0,895
Viscosity 40 °C, mm ² /s	43	68	93	140	212
Viscosity 100 °C mm ² /s	7	8,8	11	14,50	19
Viscosity Index	122	102	103	102	100
Flash Point °C	219	236	242	250	252
Pour Point °C	-33	-21	-18	-15	-9

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments