



## PRODUCT FEATURES

---

### PRO-TECH 15W40

PRO-MAX 15W40 paraffinic based mineral base oils and performance additives produced with a very high-specification gasoline and diesel engine oil is very high-tech.

### Applications

Each type of working under very difficult conditions and heavy turbo-charged gasoline and diesel and turbo engines, four-season uncharged instruments used construction and agricultural machines.

### Technical Specifications

- Thermal stability and oxidation resistance is very high,
- prevents the formation of sludge, keeping the engine clean,
- Heavy climate and road conditions, pressure drop and protects the engine,
- Extends oil change time
- High detergent and dispersant prevents debris through the engine,

### performance

API: SL / CI4	M. B. 223	MACK EO M PLUS
ACEA-E7-04	MAN M 3275	
ACEA.B404	VOLVO VDS.3	

### Typical Properties

### PACKAGING

SAE	15W40
Viscosity 100 °C mm <sup>2</sup> /s	15,13
TBN mgKOH/g	11,50
Viscosity Index	131
Flash Point °C	224
Pour Point °C	-30



SAMPIYON

## PRODUCT FEATURES

1L	PLASTIC
4L	PLASTIC
5L	PLASTIC
180 kg	DRUM



### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments