



PRODUCT FEATURES

PRO-TECH 20W50

PRO-TECH 20W/50 with the addition of paraffinic mineral base oils and special additives produced by the gasoline engine oil developed.

Applications

Gasoline-powered engines used in 4 seasons prevents the formation of high-performance foam reinforced with rust corrosion and oxidation additives that neutralize the engine oil pressure has been no reduction in the formation of deposits and soot.

performance

API: SL / CI4 M. B. 223 MACK EO M PLUS
ACEA-E7-04 MAN M 3275
ACEA.B404 VOLVO VDS.3

Typical Properties

SAE	20W/50
Density 15 °C g/mL	0.897
Viscosity 40 °C, mm ² /s	201
Viscosity 100 °C mm ² /s	20
Viscosity Index	121
Flash Point °C	222
Pour Point °C	-15

PACKAGING

1L	PLASTIC
4L	PLASTIC
5L	PLASTIC
180 kg	DRUM



PRODUCT FEATURES



Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments