



PRODUCT FEATURES

PRO-TECH 5W30

PRO-SYNT 5W30 boost in performance, superior engine protection and engine oil that provides excellent cleaning.

Applications

Passenger cars, off-road vehicle and light commercial vehicles, especially in the high-performance gasoline and diesel engines, the engine is recommended for all modern vehicles.

Technical Specifications

- High viscosity index ensures ease of operation thanks to the cold weather,
- Protects the engine against wear, rust and corrosion,
- Keep the engine clean at high temperatures providing maximum deposit control, extend service life,
- Fuel saving,

performance

API: SL / CI4 M. B. 223 MACK EO M PLUS
ACEA-E7-04 MAN M 3275
ACEA.B404 VOLVO VDS.3

Typical Properties

SAE	5W30
Density 15 °C g/mL	0.858
Viscosity 40 °C, mm ² /s	73,9
Viscosity 100 °C mm ² /s	11,9
Viscosity Index	165
Flash Point °C	222
Pour Point °C	-42

PACKAGING

1L	PLASTIC
4L	PLASTIC
5L	PLASTIC
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments