



## PRODUCT FEATURES

---

### SUPER 2T

SUPER 2T, paraffinic mineral base oil, engine oil formulated with performance additives.

#### Applications

All two-stroke air-cooled gasoline engines developed for the oil. 2-3% of the fuel mix is recommended.

#### Technical Specifications

- improves the performance of the engine, extends the life
- type of detergent-dispersant additives to help prevent deposit formation in the combustion exhaust gas is blended residues,
- Protects against rust, corrosion and form a film on the metal surfaces,
- Pre-ignition makes it easy to
- very easy to mix with gasoline,
- Oil / fuel ratio according to engine manufacturers recommendations should be made.

#### API: TC

#### Typical Properties

SAE	0.891
Viscosity 100 °C cSt	119
Viscosity 40 °C cSt	12.6
Density 15 °C\cg\m <sup>3</sup>	98
Viscosity Index	258
Flash Point °C	-27

#### PACKAGING

1 L	PLASTIC
16 kg	TIN
180 kg	DRUMS

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



## PRODUCT FEATURES

---

