



PRODUCT FEATURES

4T MAX 15W-40

4T MAX 15W-40 mineral paraffinic base oil, performance, four-stroke engine oil formulated with additives.

Applications

Four-stroke Motorcycles.

Technical Specifications

- lubricates the clutch and the transmission system effectively protects the motorcycle.
- With detergent and dispersant chemicals keeps the engine clean,
- wear, rust, corrosion and oxidation, prevents the formation of foam,
- used in wet clutch motorcycle runs smoothly.
- complete all kinds of weather and road conditions, acts.

performance

API: SJ

JASO MA

Typical Properties

SAE	15W/40
Viscosity 100 °C cSt	14,2
Viscosity 40 °C cSt	104,7
Density 15 °C\cg\m ³	0,893
TBN mgKOH/g	11,73
Viscosity Index	131
Flash Point °C	224

PACKAGING

1 L

PLASTIC

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



PRODUCT FEATURES

