

PRODUCT FEATURES

SYNTECH FULL SYNTHETIC AIR COMPRESSOR OIL

Tion all kinds of Syntech designed for use in rotary screw and vane air compressor PAObased synthetic base oils and advanced, high temperatures, even in the most demanding conditions, long life and trouble-free operation, which ensures high performance oils.

Technical Specifications

- High thermal stability
- Excellent water separation
- Resistance to oxidation
- Very good protection against rust and corrosion
- Low volatility and a very good surface property
- High viscosity index

Typical Properties

| ISO VG | 46 | 68 | 100 |
|---------------------------------|-------|-------|-------|
| Density 15 °C\cg\m ³ | 0,882 | 0.910 | 0,890 |
| Viscosity 40 °C cSt | 46 | 68 | 100 |
| Viscosity 100 °C cSt | 7,7 | 10,4 | 11 |
| Viscosity Index | 135 | 139 | 139 |
| Pour Point, ° C | 235 | 258 | 258 |
| Flash Point COC ° C | -45 | -45 | -45 |

PACKAGING

180 kg DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.