



PRODUCT FEATURES

HYDRON C SERIES (Hydraulic System Oil)

Hydron non-working hydraulic systems designed for C-series heavy duty bearings for high-speed low-viscosity hydraulic system oils.

Applications

High-speed weaving looms can be used in various applications such as a hydro-pneumatic control mechanisms and lubricants can be used for pneumatic circuit.

Technical Specifications

- Improved thermal stability,
- Very good resistance to oxidation,
- excellent protection against abrasion,
- Very good filter a feature,
- Low friction,
- Sudan good separation,

Performance

DIN 51 514 PART I

HL and DIN 51517 PART II

CEPOP PR 91H CATEGROY H2

Typical Properties

ISO	5	10	15	22
Density, 15 °C g/mL	860	860	865	868
Viscosity 40 °C, mm ² /s	5	10	15	22
Viscosity Index	90	60	70	100
Flash Point, °C	90	160	170	205

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



PRODUCT FEATURES

