



PRODUCT FEATURES

TRBLUB SERIES TURBINE OIL SERIES

SERIES TRBLUB well-refined paraffinic mineral base oils are produced by adding the appropriate additive package, long service life, high-quality oil.

Applications

Steam and water turbines, recirculating systems, hydraulic systems, compressors, used for lubrication of plain and rolling bearings. Has a high viscosity index, corrosion, foaming and reduces wear. Additives to improve water within the water can be divided into feature preserves the effective lubrication throwing.

Technical Specifications

- Special formula shows strong resistance to rust and corrosion. Extends the life of the system,
- Easily separable from water.
- Turbine bearings and gears protects against abrasion,
- preventing deposit formation caused by heat from the provides a unique description.

performance:

DIN 51 515 (R + O)

BS 489

MIL-H-17672 D

Typical Properties

ISO	22	32	46	68	100
Density, 15 °C g/mL	0,868	0,870	0,874	0,880	0,890
Viscosity 40 °C, mm ² /s	22	32	46	68	100
Viscosity, 100 °C mm ² /s	4,21	5,51	6,8	8,72	11,2
Viscosity Index	96	100	100	101	97
Flash Point, °C	188	200	220	228	235
Pour Point, °C	-18	-25	-24	-18	-13
Pass Test	Pass	Pass	Pass	Pass	Pass
Corrosion Test 100 ° C-3saat	1	1	1	1	1

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments