



PRODUCT FEATURES

COMPSOL COLD AIR COMPRESSOR OIL

COLD AIR COMPRESSOR OIL household, industrial refrigeration, cold air compressors and air-conditioners used in industrial high-quality naphthenic base oil that is very special.

Uses and Features

Thanks to a specially selected base oils and very good chemical, oxidation and thermal stability. Prevents the formation of muddy waste and pollution. Thermal stability of the pressure side to resist high temperatures, extremely resistant to oxidation, polymerization and to resin have a chemical structure.

Thanks to the high fluidity at low temperatures outside cooling system is used for general lubrication at low temperatures. Freon gases, and ammonia as the refrigerant suitable for use with R12 and R22.

Typical Properties

ISO	15	32	46	68
Density 15 °C\cg\m ³	0,880	0,892	0,897	0,902
Viscosity 40 °C cSt	15	32	46	68
Viscosity 100 °C cSt	3	4,6	5,6	7,0
Viscosity Index	45	45	45	45
Flash Point COC ° C	153	162	165	180
Freezing Point ° C	-40	-36	-33	-29

PACKAGING

180 kg DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments