



PRODUCT FEATURES

MONOREX SERIES

MONOREX series, pure mineral oils of different viscosity grades are manufactured of high quality base oils.

Applications

Very low thermal stability and oxidation resistance of carbon balance. Fixed diesel gas and dual-fuel engines, wood cutting machines, hızarlarda and used in areas where you do not need a cleaner additive. Electric motors, bearings, chains, and heat transfer machine parts akışkanlıklarında air purifiers are used at moderate temperatures.

Technical Specifications

- excellent thermal stability and oxidation resistance,
- provide effective protection thanks to high quality mineral base oils,
- provide the opportunity to use in many areas,
- Economic,
- Foam preventive features.

Typical Properties

SAE	10W	20W	30	40	50
ISO VG NO	32	68	100	150	220
Density 15 °C\cg\m ³	0.879	0.885	0.892	0.897	0.900
Viscosity 40 °C cSt	32	68	100	150	220
Viscosity 100 °C cSt	5,4	8.7	11	14.8	19,9
Viscosity Index	100	97	97	95	92
Flash Point, ° C	222	236	256	268	276
Pour Point, ° C	-15	-12	-12	-12	-12

PACKAGING

16 kg	TIN
180 kg	DRUM

Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.



PRODUCT FEATURES

