



## PRODUCT FEATURES

### FLUDS 422 20W40

FLUDS 422 20W40, tractors and construction machinery transmission, hydraulic and brake systems in some greasy oil that is recommended for use in first-class. For this reason, except for the engine lubrication system is suitable for tractors.

#### Applications

Tractors, transmission systems, braking systems, hydraulic systems and oil are used.

#### Technical Specifications

- With Additive package, excellent oxidation resistance, wear protection, to develop a foam, anti-corrosion performance
- Provides high performance hydraulic applications.
- Friction brakes regulatory additives ensures quiet operation,

#### performance

API GL-4

JOHN DEERE

MASSEY FERGUSON

FORD NEW HOLLAND

Allison C4

#### Typical Properties

<b>SAE</b>	<b>20W/40</b>
Density 15 °C g/mL	0,884
Viscosity 40 °C, mm <sup>2</sup> /s	70,4
Viscosity 100 °C mm <sup>2</sup> /s	11,2
Viscosity Index	151
Flash Point °C	220
Pour Point °C	-42

#### PACKAGING

15kg	TIN
180 kg	DRUM

#### Warnings and Suggestions

Waste oil, soil, water, sewer, and trash pour. Clean, solid and tightly sealed in a container delivered to the nearest waste oil collection center please. Keep away from children, avoid continuous and long-term contacts. If swallowed, do not induce vomiting by force, seek medical attention. Do not leave exposed to direct sunlight. Store in a closed area, Keep it away from damp and humid environments.